

SLIDING GATE RANGE

9000A Automatic Sliding Gate



Automatic | Compliant | Plug & Play



Features

- 100% duty cycle heavy industrial usage
- BS EN 12453 Peace of mind for safety
- Single Phase Supply
- Plug & Play installation
- Programmable control panel c/w fault diagnostic on screen display
- Highest specification of components are ONLY used
- Seamlessly forms part of the existing fence lines perimeter security
- Aluminium construction for long lasting and maintenance free performance
- MANY different infill's available to match clients exacting requirements
- Error log is stored in the control panel for fault diagnosis
- A VERY easy to use manual release mechanism which requires no tools in the event of power failure.

9000A Added Benefits

- Ease of installation
- Low maintenance
- 99.9% Access Control compat
- Pedestrian input as standard
- Fire Alarm Input pre-configured
- Designed and built to last
- Easy to use for end users

Optional Extras

- Razor Wire Extensions
- Electric Fence
- Anti-Climb Spikes
- Traffic Lights
- Warning Siren
- Timber Infills
- Louvre Infills

The 9000A Automatic Cantilever Sliding Gate complies with BS/EN 12453. The gate portal is fitted with dual height photocells and 6 category 3 monitored live safety edges.

The gate is controlled by a purpose made German Feig control panel, single phase supply, via an integrated frequency converter controlled output to a 3 phase motor. This can be configured very easily for all the standard program modes including no passage time outs & free exit and entry loops to name a few. As standard the control panel can accommodate pedestrian

open signals, airlock systems and much more. The gate's movement is controlled via a rack & pinion system monitored by an encoder. This allows for a precise and controlled operation that is robust and dependable.

Our gates are delivered on a vehicle equipped with a crane, fully assembled, ready to bolt down continuing our "plug & play" ethos.

This minimises disruption on site and ensures a smooth, quick and easy installation.

We have developed the gate using aluminum construction with its obvious anti-corrosion properties/strength and longevity in mind.

Trusted by many in the industry as the ultimate sliding gate it can be clad with a HUGE range of infills to suit the existing perimeter fence line.

9000A Automatic Sliding Gate

01977 701566

info@gmcfabservices.co.uk



www.gmcfabservices.co.uk

SLIDING GATE RANGE

9000A Automatic Sliding Gate



Automatic | Compliant | Plug & Play



Product Specifications

Gate Speed	3 to 6 Seconds Per Metre (Speed WILL vary dependant upon gate size/Infill etc)
Duty Cycle	100% Heavy Industrial Usage Suitable for Indoor & Outdoor Usage
Specification	CE Approved, TUV Approved
Power Requirements	Single Phase 240v 50Hz 10 Amps
Colours	All RAL Colours Available (Non Standard RAL's Optional Cost)
Maximum Span Dimensions	12m Clear Drive Through Opening
Maximum Height Dimensions	2.4 Metres (Max Width 12m) 3.0 Metres (Max Width 10m)
Material Construction	Aluminium Construction of Gate Leaf and Main Tower Tower Top/Base plate Wheel Carriages Zinc Plated Steel
Unit Weight	560Kg Approx (dependant upon gates size and infill type)

*All gates are bespoke and manufactured to order.

Industry Standard

Our gates have been classed as the best in the industry. It has been designed to last using the best materials and components that we can buy. As with all our products they are 100% DutyCycle.



Absolute Control

The 9000 Sliding Gates feature a Feig control panel that is far more advanced for safety and motion than its rivals.



9000A Automatic Sliding Gate